

**PRICE QUOTATION**

from: **CONTIMADE s.r.o.**  
**Č.p. 104, Kaňovice 763 41, okr. Zlín**

fax: + 420 577 119 161  
 phone: + 420 576 779 170  
 email: firma @contimade.cz

company: **Requested from:Michal Kudrnovský**  
**Ystad Trading**  
 phone:  
 fax:  
 email: info@relaxovat.cz

**Number of price quotation:Ystad Trading\_17\_0208**

*We would like to ask you to mention generally our above – referenced number of price quotation during our correspondence*

**Price Quotation****Project: Ystad Trading\_17\_0208**

PL

**Container á 6 058 x 2 435 x 2 820 mm ( IH 2 500 mm )****2 pc****Steel frame**

- welded construction of steel, pre-treatment: **grit blasting**, **circuit bottom console with zinc-coated external side**, anticorrosion treatment, 1x basic paint, 2x cover paint outside; PUR 2-components polyurethan paint
- the same colour shade like the outside walls with forklift-truck openings (slots)
- length of the forklift-truck must be 2500 mm minimally!

**2 pair****Roof**

- roofing: zinc-coated trapezial metal plate th. 0,75 mm, unpainted, ventilated roof with minimum slope, gutter drain with 2 pcs in-built downpipes, nominal bore 63 mm
- payload of roof: 1,5 kN/m<sup>2</sup>
- thermal insulation: mineral wool **A1 (EN 13501-1) - 100 mm,  $\lambda = 0,039$**

roof

**Ceiling**

- vapor barrier: PE - foil th. 0,2 mm
- inside coating: double-sided laminated chipboard E1, th. 13 mm, **white**

**Walls**

- outside coating: zinc-coated trapezial metal plate th. 0,55 mm, standard colours **RAL 7035 - light grey**
- thermal insulation: mineral wool **A1 (EN 13501-1) - 60 mm,  $\lambda = 0,039$**
- inside non carrying construction: **wooden** construction
- vapor barrier: PE - foil th. 0,2 mm
- inside coating: double-sided laminated chipboard E1, th. 13 mm, **white**
- partition walls: 86 mm, double-sided laminated chipboard E1, th. 13 mm, with insulation th. 60 mm from glass wool, for inside height 2 500 mm

**6,25 rm****Floor**

- bottom covering: zinc-coated steel metal plate th. 0,55 mm
- thermal insulation: mineral wool **A1 (EN 13501-1) - 100 mm,  $\lambda = 0,039$**
- vapor barrier: PE - foil th. 0,2 mm
- chipboard E1 - th. 22 mm
- cement-chipboard, th. 22 mm 15 m<sup>2</sup>
- floor covering: PVC, th. 1,4 mm, grey, marble, with plastic skirting board
- **connection of floor and floor covering with floor parts**
- payload of floor: **2,5 kN /m<sup>2</sup>**

### Window standard, made of plastic, insulating - glazing, white frame

- window 1 210 / 1200 mm, opening/tilting, U =1,1 W/m<sup>2</sup>K 3 pc
- window 575 / 400 mm, tilting, ornamental glazing,  $u=1,1 \text{ W/m}^2 \text{ K}$ ,  
without external roller blind 1 pc
- external roller blind, made of plastics, for window 1 210 / 1 200 mm, white 3 pc

### External door - ZK

- door wing: zinc- coated with filling, steel
- doorframe
- inside paint RAL 9010, outside paint -the same like at the container
- black plastic door fittings
- cylindrical lock with 3 keys
- steel door: clear opening dimension 811 / 1 968 mm 1 pc

### Interior door

- door wing: zinc - coated, filling - paper honeycomb, zinc- coated doorframe, standard colour RAL 7035, 9010, ALU- fitting (short doorplate), common lock + one key
- WC door-fittings 1 pc
- dimension: clear opening dimension: 561, 686, 811 / 1 968mm 1 pc
- dimension: clear opening dimension: 561, 686, 811 / 1 968 mm connecting doorframe between 2 containers 2 pc

### Sanitary equipment

- water pipeline : water supply - plastic pipes (PP),
- sewage - plastic - HT piping -
- pipeline conducted over wall
- water distributions connection through the wall or through the floor, stop valve 3/4", reduction valve with manometer 3/4" 1 pc
- sewage ventilation, ventilation pipe inside sanitary room 1 pc
- porcelain toilet with flushing system, plastic seat and cover, toilet paper holder, plastic hook 1 pc
- porcelain washbasin cca. 500x350 mm, with sink mixer tap - cold and hot water, plastic siphon trap, mirror 400x300 mm, glass shelf, plastic hook for clothing 1 pc
- shower box: made from plastic, dimensions 800x800 mm, curtain, shower mixer tap, soap shelf 1 pc
- electric boiler 80 l, type Trend, 1/N/PE -220V, product of. AEG, mounted completely with solid connection 1 pc
- mini kitchen (chipboard): stainless steel sink top, kitchen sink with cold and hot water mixer tap, one 2-hotplate cooker, refrigerator 102 litres, dimensions: 1 000 x 850 x 500 mm, 3 pcs of electric sockets, thereout 1 of them is extra secured 1 pc
- plastic gully with siphon trap, joined to the drain pipe from side of customer 1 pc

### Electric installation - according to DIN norms

- electric switchboard with circuit breaker and current protectors 2 pc
- CEE 32 A 2 pc